

DÜSENLISTE

| Düsensatz | A | B | C | D | E | F |
|--|--------------|--------------|-----------------------------|-----------------------------|--|----------------------------|
| Nadel Ø Artikelnummer | 2.5 2021A | 3.1 2021B | 5.0 2022 + 8064CD | 5.0 2022 + 8064CD | 6.5 2022 + 8064E | 7.5 2022 + 8064F |
| Materialdüse Ø Artikelnummer | 2.2 2035A | 2.8 2035B | 3.9 2035C | 4.5 2035D | 6.0 2035E | 6.8 2036F |
| Luftdüse Nr. 2029 Ø | 3.6 A | 4.2 B | 5.3 C | 6.0 D | 7.45-10 E 7.65-10 E0 7.65-12 E1 8.00-12 E2 (8.25-12) E3 | 8.90-14 F |
| Konus Ø | 10 | 10 | 10 | 10 | | |

Beispiel für Pistole mit Düsensatz E

- Nadel: Ø 6.5 (2022 + 8064E)
- Materialdüse: Ø 6.0 (2035E)
- Luftdüse: Ø 7.65-12 (2029E1)
- Aussendüse: 2032-22 oder 2033-25

| Aussendüse | Nr. | 2 | 2 | | | | Schlitzbreite (mm) | Spritzbreite (cm) | Anwendung | |
|---|-----|---|---|-------|-------|---------|--------------------|-------------------|----------------------|----------------------|
| Rostfreier Stahl = 2032- Karbide = 2033- | | | | 11 | 11 | | 2.0 | 8 - 18 | Standard | |
| | | | | 12 | 12 | | 3.0 | 10 - 16 | grosse Leistung | |
| | | | | 3 - 3 | 3 - 3 | | 2.5 | 8 - 18 | grosse Leistung | |
| | | | | 4 - 4 | 4 - 4 | | 2.0 | 10 - 16 | Standard | |
| | | | | 5 | 5 | | 2.0 | 14 - 25 | Standard | |
| | | | | 6 - 6 | 6 - 6 | | 2.0 | 22 - 40 | Standard | |
| | | | | | 8 | | 2.5 | 10 - 16 | grosse Leistung | |
| | | | | | 50 | 50 | 2.5 | 25 - 40 | grosse Leistung | |
| | | | | | 52 | 52 | 2.0 | 12 - 18 | grosse Leistung | |
| | | | | | | | 2.0 | 15 - 25 | grosse Leistung | |
| | | | | | | | 20 - 20 | 2.5 | 10 - 15 | grosse Leistung |
| | | | | | | | 21 | 2.5 | 15 - 23 | grosse Leistung |
| | | | | | | | 22 | 3.0 | 15 - 23 | sehr grosse Leistung |
| | | | | | | | 23 | 2.5 | 20 - 40 | grosse Leistung |
| | | | | | | | 24 | 2.5 | 50 | Standard |
| | | | | | | 25 - 25 | 2.5 | 50 | Standard | |
| | | | | | | | 3.0 | 10 - 18 | sehr grosse Leistung | |
| | | | | | | | 40 | 3.0 | 10 - 16 | grosse Leistung |
| | | | | | | | 42 | 3.8 | 10 - 25 | sehr grosse Leistung |
| | | | | | | | 44 | 3.5 | 25 - 35 | sehr grosse Leistung |
| | | | | | | | 421 | 4.3 | 10 - 25 | extreme Leistung |

| Konus | Ø | 10 | 12 | 14 |
|------------|-----|---------------------------------|----------------------------------|--------------------|
| Aussendüse | Nr. | 2, 3, 4, 5, 6, 8, 11, 12, 50 | 20, 21, 22, 23, 24, 25, 52 | 40, 42, 44, 421 |