



LOW PRESSURE PAINT GUN WITH ATOMIZING AIR

This paint gun, completely made of stainless steel, is compatible with all kinds of products.

CONNECTIONS:		PAINT NOZZLE:
Opening air	1/4 "	Ø 2 to 6.2 mm
Atomizing air Paint inlet	3/8 " 3/8 "	AIR NOZZLE:
Ø passage of paint	11 mm	Ø 4.5 to 7.8 mm

EXTERNAL NOOZLES

A wide choice of external nozzles in stainless steel or in carbide is available, to meet all your needs in line width and performance. The carbide nozzles have a much longer durability than the stainless steel ones (about 4 times). The choice of the external nozzle depends on the diameter of the paint nozzle (see the list of nozzles on our website).

An inlet is provided for flushing the head of the gun (recommended for water-based paints). The plug of this inlet will be replaced by a connection (on request). In order to limit the width of the line, a system made of tungsten carbide can be fixed on the gun (option).

RECOMMENDATIONS

- For paint connection, use a hose with inner Ø of 13 mm (small machine) and of minimum 16 mm (big machine)
- For atomizing air, use a hose with inner Ø of 10 mm
- To get good performance, use an air atomizing pressure lower than the pressure in the tank
- Use an opening air pressure of at least 6 bar (87 psi) and an air atomizing pressure of maximum 5 bar (72 psi)

SPECIFICATIONSDimensions:185 x 80 mmWeight:1.5 kg

Edwin Kamber SA reserves the right to change at any time this information



