



HIGH PRESSURE PAINT GUN WITHOUT ATOMIZING AIR

This paint sprayer, completely made of stainless steel, is compatible with all kinds of products. It can be fitted with a special connector for rinsing.

CONNECTIONS:

Opening air	1/4 "
Closing air	1/4 "
Paint inlet	3/8 "
Ø passage of paint	11 mm

PAINT NOZZLE:

Ø 3.2 mm in carbide

The sprayer features a double-acting system (pneumatic opening and closing) for ultra-fast action and is equipped with 2 inlets. Suitable for medium and large machines or trucks (rapid exhaust of opening air).

EXTERNAL NOZZLES

A wide choice of external nozzles, only in tungsten carbide, is available to meet all your needs in line width and performance. For this gun, there are flat nozzles or reversible nozzles available. The guard of the reversible nozzle is compatible with all existing switch tips brands. The choice of the external nozzle depends on the kind of work to be done (please ask us for the choice of the diameter and the spraying angle).

An adjustable ramp can be fixed on the gun for lines up to 60 cm (option). Bigger widths are possible on request. This option is very useful for marking on crosswalks and airports.

RECOMMENDATIONS

- For paint connection, use only a hose that can tolerate a working pressure of 300 bar (4350 psi)
- Use a constant opening air pressure of at least 5.5 bar (80 psi)

SPECIFICATIONS

Dimensions:	170 x 90 mm
Weight:	1.3 kg

Edwin Kamber SA reserves the right to change at any time this information

